



EN ISO 20345:2011



RITMO
CUBAN HIGH
91370-00L

S3 SRC

Size: 35-48
Weight: 570 gr.

Fit: 11

Working Environment:
Finishing-off building,
Components and Automotive,
Logistics and Light Industry, ESD
Areas



FEATURES

UPPER
MicroFiber Suede with Pro-tech
SXT light

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Five 4 Fit

TOE CAP
Alu SXT 2.0 Toe cap

RESISTANCE TO PERFORATION
Zero(K) Perforation resistant

TYPE
Ankle boot

SOLE
PU / PU ESD-PLUS SRC
Double density PU sole, Outer- and
in-between sole with ESD
compound. For use in contact with
sensitive electronic equipment.
Light and comfortable, very
versatile, highly non-slip SRC
Antislip standard.



SRC (SRA+SRB)



		SOLE 91 PU - PU
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	0.54
	HEEL (CONTACT ANGLE °) ≥0.28	0.52
SRB STEEL + GLYCEROL	FLAT ≥0.18	0.29
	HEEL (CONTACT ANGLE °) ≥0.13	0.23

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole
FIVE 4 FIT

Highly breathable and absorbent
anatomic insole. Multilayer structure
to take advantage of the peculiarities
of each component. Dry and with a
comfortable memory foam "pillow"



Protection elements
ZERO(k)
ANTIPERFORATION **alu-sxt2.0**
aluminium

A new aluminium multi-thicknesses
toecap, which delivers a highly
performing protection where needed.
Resistant to impact of over 200J. Non
Metallic anti-perforation insert.
Resistant to over 1100 N with zero
perforation.



Lateral stability
dynamic HC control
technology

Ergonomic rigid internal structure. It
houses the heel into the right seat,
adjusting the foot support and control
of the ankle sideways movements. It
keeps the foot tight to the shoe,
allowing the perfect fit.



Torsional stability
STABIL ACTIVE

Support made of rigid plastic
material. It stabilizes the heel bone,
the instep and tarsal joints, without
altering energy absorption. A support
for the natural movement of the foot;
it provides comfort and greater
stability.



Electrical features



ESD footwear discharge static
electricity and avoid damaging
surrounding objects; they are
designed in compliance with the
following standards: IEC EN
61340-5-1:2016 - IEC EN
61340-4-3:2018 - IEC EN
61340-4-5:2018.

Other

Strip with 4 filaments of carbon fiber,
ensuring proven anti-static properties
of the footwear over time.